


# Abrasive Metering System FEEDLINE IV

## Optimised abrasive consumption for customised applications



Stable and repeatable operating parameters are a fundamental requirement for high-quality waterjet cutting. This applies in particular to abrasive applications used to cut brittle materials, where a constant flow of abrasive is simply a must. KMT WATERJET SYSTEM responded to this demand by developing the FEEDLINE IV abrasive metering system. Controlled through a central CNC controller or a potentiometer, the FEEDLINE IV supplies the cutting head with the optimized flow of abrasive. This helps save material and costs.

### The FEEDLINE IV technology

The FEEDLINE IV system supplies the cutting head with a constant metered quantity of abrasive. Without this controlled supply, the mixing chamber for abrasive, air and water would become clogged up. With the FEEDLINE IV, this is effectively prevented. It feeds a metered flow of abrasive by means of compressed air into a 0.8-litre transfer tank. At the base of the tank, the abrasive collects on the metering and transfer wheel whose rotational speed determines the feed rate to the cutting head.

### New design of abrasive outlet and control unit

The new abrasive outlet consists of a single component, facilitating maintenance as there are no moving parts. A bypass opening in the outlet component significantly reduces the risk of cutting water entering the plastic hose through which the abrasive is transferred to the cutting head. This prevents water entering the FEEDLINE IV housing. The metering wheel of the FEEDLINE IV is equipped with a shaft seal preventing water from entering the control unit. The housing lid of the metering wheel and the control unit are transparent, so that operators can easily detect any problems occurring in the unit.

### Lower costs thanks to accurate control

Different materials to be cut require different quantities of abrasive. The thicker the material, the more abrasive is needed. Accurate metering settings help lower operating costs

especially in units used to cut many different materials on a daily basis. The adjustment range of the FEEDLINE IV caters for flow rates of 0 to 1,000 g per minute. Greater quantities can be catered for by changing a shim.

### Suitable for integrated or stand-alone control

Standard feed rates can be stored in the CNC controller and transferred to the FEEDLINE IV. Alternatively, the FEEDLINE IV operation can be controlled by means of a potentiometer. Each cutting head is thereby supplied by a separate FEEDLINE IV.

### Lightweight and compact design for easy installation

The FEEDLINE IV module weighs only 3.1 kg and can thus be mounted directly onto the motion system of the waterjet cutting unit. The abrasive hose connecting the metering unit to the cutting head is therefore kept very short, which is an advantage, as long hose length result in poor cuts.

>>>





#### Technical data

Flow rate (adjustable*)	0–1,000 g/min
Operating voltage	24 VDC
Control voltage	0–10 V / 4–20 mA
Net weight	3.1 kg
Length	124 mm
Width	130 mm
Height	470 mm

\* Flow rates of greater than 1,000 g/min can be achieved by replacing a shim.

#### AMS III abrasive management system


The FEEDLINE IV is an integrated component and therefore designed for use in conjunction with the AMS III abrasive management system. It consists of an ABRALINE III abrasive feed unit supplying up to four FEEDLINE IV metering modules with abrasive. These can be individually controlled to supply the connected ACTIVE AUTOLINE™ II / IDE™ cutting heads with abrasive. The perfect coordination of these components results in precision cuts and makes the system particularly reliable and economical.

#### Improved features of the FEEDLINE IV:

- Redesigned abrasive outlet section
- Watertight control unit housing
- Flexible adjustment of control parameters to meet customer requirements
- Reduced module weight
- Transparent lids over electronics and metering wheel
- Powder-coated housing

#### Online Shop ORDERLINE ANYWHERE

As a registered customer, you can now order original KMT spare parts online through our ORDERLINE ANYWHERE portal. Simply look up your part in the electronic spare parts catalogue and add it to your virtual shopping basket. In addition, you can track your orders online and make use of a number of other useful functions.



- 1 Abrasive inlet
- 2 Air filter of abrasive inlet
- 3 Abrasive transfer tank
- 4 Air filter of transfer tank
- 5 Housing of feed system
- 6 Motor
- 7 Abrasive outlet



**KMT GmbH • KMT Waterjet Systems**

Auf der Laukert 11 • 61231 Bad Nauheim • Germany  
Phone: +49-6032-997-0 • Fax: +49-6032-997-274  
[www.kmtgroup.com/waterjet](http://www.kmtgroup.com/waterjet) • [info-waterjet@kmtgroup.com](mailto:info-waterjet@kmtgroup.com)

